



Performing with cutting-edge finesse...

## **CABIPA ATF AUTOMATIC TRANSMISSION FLUID DEXRON III**

### **Description**

**CABIPA PREMIUM ATF DEXRON III** is a specially formulated fluid designed to meet the requirements of a broad range of automatic transmission specifications. It is based on a blend of high viscosity index oils and proven additives, to provide long term protection in units requiring a non-friction modified type fluid. Its premium synthetic blend formula exceeds DEXRON® III requirements. Specially selected friction modifiers allow friction retention for long life performance, whilst enhanced oxidation, thermal stability and corrosion resistance ensure long mileage component protection. Suitable for automobiles, trucks, mobile hydraulic equipment, automatic or power shift transmissions, clutches and power steering wheel gear boxes.

### **Properties**

- Premium synthetic blended formula that exceeds DEXRON®-III requirements.
- Its specially selected friction modifiers allow friction retention for long life performance.
- Enhanced oxidation, thermal stability and corrosion resistance ensure long mileage component protection.

### **OEM Approvals and Specifications**

- GM DEXRON®-III
- ZF TE-ML-14
- Ford MERCON
- MB Page 236.5
- Allison C-4
- MB Page 236.9
- Voith G 607



Performing with cutting-edge finesse...

## Technical Specification

Test	Unit	Method	Typical Values
Density @ 15°C	g/cm <sup>3</sup>	ASTM D4052	0.87 – 0.88
Flash Point	°C	ASTM D92	Min. 200
Pour Point	°C	ASTM D97	Max. -15
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D445	33.8
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D445	6.2
Viscosity Index	-	ASTM D2270	135
Colour	ASTM	ASTM D6045	5.5
Total Acid Number (TAN)	mgKOH/g	ASTM D664	-
Total Base Number (TBN)	mgKOH/g	ASTM D2896	-
pH	-	-	-

## Packing Information

12x1L